

KSK 30

30 kVA RICARDO-KOFO SERIES ENGINE GENSET



GENERAL SPECIFICATIONS

Standby Power	kVA	30
	kW	24
Prime Power	kVA	27
	kW	22
Frequency	Hz	50
Rated Speed	rpm	1500

FUEL CONSUMPTION

% 100 Fuel Consumption	lt/h	9
% 75 Fuel Consumption	lt/h	6,5
% 50 Fuel Consumption	lt/h	4,7

GENSET DIMENSION and WEIGHT

CANOPY TYPE

Length	(L)	mm	2300
Width	(W)	mm	1000
Height	(H)	mm	1590
Weight	(H)	kg	871
Fuel Tank Capacity	lt		163

OPEN TYPE

Length	(L)	mm	2300
Width	(W)	mm	1000
Height	(H)	mm	1310
Weight	(H)	kg	688
Fuel Tank Capacity	lt		163

TECHNICAL SPECIFICATIONS

ENGINE

(ESP) Standby Power	kW/kVA	30,1/37,6
(PRP) Prime Power	kW/kVA	33,1/41,4
Brand		KOFO
Model		N4100DS-30
Type		4 Stroke
Injection Type		Direct
Cylinder Bore and Stroke	mm	100*115
Displacement	lt	3,61
Compression Ratio		17:01
Aspiration Type		Natural
Rated Speed	rpm	1500
Total Oil Capacity	lt	13
Total Coolant Capacity	lt	17
Cooling System		Water Cooled
Governor Type		Mechanical

ALTERNATOR

Brand		KOCSAN
Model		NF-184G
Phase		3
Output Voltage	V	230 / 400
Frequency	Hz	50
Automatic Voltage Regulation	±%	1
Standby Power	kVA	30
Power Factor	Cos ϕ	0,8
Protection Class		IP 22
Insulation Class		H
Overload Running Time		%110 for 1 hour
Efficiency with Cos ϕ :0,8 and %75 Load	%	88

TECNHNICAL SPECIFICATIONS

CANOPY and CASE

- Easy Lifting and Carrying Design
- Emergency Stop Push Button Mounted on Exterior Casing
- Electrostatic Polyester Powder Coated Paint
- Special Design for Minimizing Acoustic Level
- Transparent Cover for Monitoring Control Unit
- Vibration Insulator

D300 CONTROL UNIT

- Webbased Control Unit with Additional External Slot
- Parameter Regulation via USB, RS-232 and GPRS
- CANBUS-J19398 & MPU Input
- 8 pcs. Configurable Digital Inputs
- 6 pcs. Configurable Digital Outputs
- 3 pcs. Configurable Service Alarm
- 3 pcs. Configurable Analog Inputs
- Language Configuration
- Weekly Working Program
- Free PC Configuration Software
- Remote / Manuel Start Controller
- ATS & AMF with Uninterrupted Transfer
- Modbus RTU
- Modbus TCP/I
- Internet Central Monitoring (Optional)
- Sms & E-mail Sending (Optional)

OPTIONAL EQUIPMENTS

- | | |
|-----------------------------------|------------------------------------|
| - Super Silent Canopy | - Different Canopy and Case Colour |
| - Trailer | - Fuel & Oil Heater |
| - Automatic Fuel Filling System | - External Fuel Tank |
| - Remote Monitoring | - Electronic Governor |
| - 3P / 4P Circuit Breaker | - 3P / 4P ATS Panel |
| - Synchronization System | - Expandable Fuel Tank |
| - Alternator with Two AVR and PMG | - Fuel / Water Separation Filter |